





SW12SM MONSTER ELECTRIC CUTTING UNIT



SW12SMonster. The most powerful cutting unit for Technical Textile & Composite.




ELECTRIC CUTTING UNIT

WHAT'S NEW:

New 350 W heavy duty motor Extra strong torque optimized steel/brass gears Central knife guidance New main power switch with Led Easy fixing structure for O.E.M applications Low-friction Teflon[®] coated foot












TECHNICAL DETAILS:

Blade diameter: 120 mm (4.7"), with hard metal counterblade Blade equipped: 12SHSS, 8-edges, HSS steel Blade speed: 500 r.p.m. Cutting ability: up to 50 mm (2") Power: single phase – 350 W Max. absorption: 2.5 A Net weight: 3300 g (with power supply cord) Total weight (with packing box): 5500 g Electric cable length: 1.5 mt (with no plug) Minimum brightness for working operations: LUX 200 Vibrations at start up: < 2.5 m/sec 2 Temperature range: 0 – 55 C Umidity range: 10 – 95% without condensate



Dimension layout

BLADES AVAILABLE:

12SHSS, 120 mm 8-edges, HSS steel | **12CSW**, 120 mm circular, EXTRA steel | **12DHSS**, 120 mm 12-edges, HSS steel | **12SHSSTF**, 120 mm 8-edges, HSS steel | **12SHSSTF**, 120 mm 8-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12SMD**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coated | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coateel | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coateel | **12DHSSTN**, 120 mm 12-edges, HSS steel Titanium coateel | **12DHSSTN**



FOLLOW US:



RASOR ELETTROMECCANICA SRL

Via Vincenzo Caldesi 6 20161 Milan · Italy ph. +39 02 66 22 12 31 fax +39 02 66 22 12 93 info@rasor-cutters.com

www.rasor-cutters.com